

OPT-2200A(LFP) Gigabit Media Converter

10/100/1000Base-Tx to GE SFP

RoHS Compliant



>>Description

The OPT-2200A series comply with IEEE 802.3/ab Gigabit Ethernet standard. It supports two types of media for network connection such as 10/100/1000 Base-T to 1000 Base SX/LX and connects these two types of segments to operate smoothly. OPT-2200A series can be used in 14 slot chassis as plug-in module. OPT-2200A series Fiber Media Converter transforms 1000Base-T (Copper Gigabit) media to 1000Base-SX/LX (Fiber Gigabit) media and vice versa. The 1000Base-T port supports full-duplex Gigabit connection at wire speed with RJ45 connector. The fiber Gigabit connection supports shortwave (SX) or long wave (LX) laser optic with multi-mode or single-mode SFP type connector.

This converter will give your Copper Gigabit connection the ability to interface with fiber connection over a distance up to 80 km! 10/100/1000 means, that media converter that converts the electrical signal of a 10/100/1000 Ethernet signal from copper to fiber. This solution will offer a low-cost integration option for network managers who want to migrate from 10/100 networks to Gigabit Ethernet. Gigabit only switches can now be connected to 10/100 networks without the need to upgrade the 10/100 side, allowing network managers to add new equipment gradually.

>>Main Features

- Complies with IEEE 802.3, IEEE 802.3u, IEEE802.3z, IEEE802.3ab, IEEE 802.3x auto-negotiation
- Works at 10Mbps or 100Mbps, full or half-duplex mode, or 1000Mbps full-duplex mode
- One SFP slot for Gigabit links
- Extends distances ranging from 550m(multi-mode fiber) to 120km(single-mode fiber)
- Supports auto MDI/MDIX function
- Status LED for easy monitoring of device status
- Supports jumbo frame size 9K bytes
- Supports independent LFP function
- External power supply
- FCC Class A & CE approved



>> Specifications

Interface

- 1 x Ethernet port (RJ45) 10/100/1000Base-Tx
- 1 x Optical port (SFP) 1000Base-Fx

Optical Port

- Available for 1310nm and 1550nm Single mode, and 850nm Multi mode;
- Transfer Distance: up to 120km;
- Connectors: SFP
- Fiber core: 9/125µm on single mode fiber, 50/125µm and 62.5/125µm on multi-mode fiber

Ethernet Port

- Standard: IEEE802.3, IEEE802.3u, IEEE 802.3ab, IEEE802.3x
- Available speed: force 10Mbps, force 100Mbps, force 1000Mbps and auto-detective 10/100/1000Mbps Full-Duplex and Half-Duplex auto-negotiation
- Connectors: RJ-45 Connector; MDI/MDI-X connection auto-sensing

DIP Switch Function

- TP port mode Normal or Cut-Through
- LFP LFP enabled (default) or disabled

LED Indicators

- Power Status, FDX, Speed, FX Link/Act, TX Link/Act

Power Requirement

- Input: 5V DC

Physical Characteristics

- Housing: Metal enclosure
- Dimensions: 94 x 70 x 26mm (Excluding the connector)
- Weight: 0.28kg

Environmental Limits

- Operating Temperature: 0°C to 50°C
- Storage Temperature: -20°C to 70°C
- Operating Humidity: 10% to 90% RH
- Storage Humidity: 5% to 90% RH

Agency Approvals

- FCC Part 15 of Class A & CE approved

Warranty

- 3 years

>> Ordering Information

| | |
|-----------|--|
| OPT-2200A | 10/100/1000Base-Tx to GE SFP Fiber port, LFP |
|-----------|--|

>> Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTONE before they become applicable to any particular order or contract. In accordance with the OPTONE policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTONE or others. Further details are available from any OPTONE sales representative.

sales@optone.net
<http://www.optone.net>

Edition FEB 10, 2022
Published by Optone Technology Limited
Copyright © OPTONE
All Rights Reserved