

OPT-2206 Fiber Switch

2*GE SFP ports to 4*10/100/1000Base-Tx
RoHS Compliant



>>Description

The switch provide 4-port 10/100/1000M RJ45 and 2-port 1000M SFP fiber ports, user may need to use different SFP modules, such as 1000Base-T, 1000Base-SX, 1000Base-LX and so on. Switch by the United States the latest Marvell IC, stable performance and excellent quality, with a higher cost performance. For small optical Ethernet and optical network with special needs.

>>Main Features

- Complies with IEEE802.3, IEEE802.3u/ab/z standard
- Provides 4-port 10/100/1000M RJ45 and 2-port SFP fiber ports
- Supports auto duplex(HDX/FDX) auto MDI/MDIX function
- SFP port supports 1000BASE-SX/LX modules
- Supports 802.3x flow control
- Optional VLAN function
- Supports jumbo frame size 10K bytes
- Status LED for easy monitoring of device status
- FCC Class A & CE approved

>> Specifications

Interface

- 4 x Ethernet port (RJ45) 10/100/1000Base-Tx
- 2 x Optical port (SFP) 1000Base-Fx

Optical Port

- Available for 1310nm and 1550nm Single mode, 850nm Multi mode
- Transfer Distance: up to 120km
- Connectors: SFP
- Fiber core: 9/125µm on single-mode fiber; 50/125µm and 62.5/125µm on multi-mode fiber

Ethernet Port

- Cable: Cat 5/5e/6 UTP cable
- Available speed: force 10Mbps, force 100Mbps, force 1000Mbps and auto-detective 10/100/1000Mbps. Full-Duplex and Half-Duplex auto-negotiation
- Connectors: RJ-45 Connector; MDI/MDI-X connection auto-sensing

Standard

- IEEE802.3 (10Base-T)
- IEEE802.3u (100Base-TX/FX)
- IEEE802.3ab (1000Base-T)
- IEEE802.3z (1000Base-SX/LX/CX/T)

- IEEE802.3x (Flow control)

LED Indicators

- Power Status, FX Link/Act, TX Link/Act

Switch Properties

- MAC Table: 16K
- Packet Buffer: 2Mbit
- Switching Delay: <5µs

Power Requirement

- 12V DC, External AC to DC adapter

Physical Characteristics

- Housing: Metal enclosure
- Dimensions: 214 x 105 x 32mm
- Weight: 0.6kg

Environmental Limits

- Operating Temperature: -10°C to 70°C
- Storage Temperature: -20°C to 70°C
- Operating Humidity: 10% to 90% RH (non-condensing)
- Storage Humidity: 5% to 90% RH (non-condensing)

Agency Approvals

- FCC Part 15 of Class A & CE approved

Warranty

- 3 years

>> Ordering Information

OPT-2206 2*GE SFP Fiber ports to 4*10/100/1000Base-Tx, VLAN Optional

Optional SFP

Model	Rate	Wavelength	Distance	Connector
SFP-SX-MM-0205	1.25Gbps	850nm	0.5km	LC
SFP-LX-SM-0220	1.25Gbps	1310nm	20km	LC
SFP-LX-SM-0240	1.25Gbps	1310nm	40km	LC
SFP-ZX-SM-0280	1.25Gbps	1550nm	80km	LC

>> Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by OPTONE before they become applicable to any particular order or contract. In accordance with the OPTONE policy of continuous improvement specifications may change without notice.

The publication of information in this data sheet does not imply freedom from patent or other protective rights of OPTONE or others. Further details are available from any OPTONE sales representative.

sales@optone.net
<http://www.optone.net>